

BS Vertriebsbüro GmbH

Silo-Anlagenbau - "Your specialist in silo components"

Pillauer Str. 2 · D-74336 Brackenheim
Fon ++49 (0)7135 12409 · Fax ++49 (0)7135 933599
e-mail: info@bs-vertrieb.de

[Home](#)

[e-mail / Contact](#)

[Impressum](#)

[Allgemeine Geschäftsbedingungen](#)

Jet Loaders + Loaders / chute

- [Jet-Loader Quadro
Type JBM 220](#)
- [Jet Loader Rondo
Type JBM 250](#)
- [Jet Loader
Tele-Rondo
Type JBM 200](#)
- [Gravel loader
Rondo Type DN 500,
600, 800](#)
- **Variable dust skirt
Type Rondo 250**
- [Big-Bag-
filling System](#)
- [Big-Bag-
discharge system](#)
- [Impeller packer for
valve bags](#)
- [Bucket elevators](#)
- [Bucket conveyors](#)
- [Concrete block
making machine
ABS](#)

Variable Dust Skirt for Jet Loader Type Rondo 250



Areas of application

The variable dust skirt is used when loading open vehicles with the loader type RONDO 250. It facilitates the optimum dust exhaust conditions during open vehicle loading. With silo vehicle loading the loading spout can be led into the silo dome opening.

Functioning mode

The dust skirt, which is suspended with claws on the loading head, can be electro-pneumatically unlatched during open loading. When lowering the loading spout the dust skirt is lowered as well. The dust created at the loading spout through the discharged bulk goods is confined by the dust skirt and can be fed into a dust removal plant.

When loading silo vehicles the variable dust sleeve remains in its upper position and the setting cone can be led unhindered - by hand in an emergency - dome opening.

Material/design

Steel construction, dust skirt of rubberized fabric with ring holder

Advantages

- Optimum dust exhaust
- Simple handling

[→ back to product survey](#)

