

BS Vertriebsbüro GmbH

Silo-Anlagenbau - "Your specialist in silo components"

Pillauer Str. 2 · D-74336 Brackenheim
Fon ++49 (0)7135 12409 · Fax ++49 (0)7135 933599
e-mail: info@bs-vertrieb.de

[Home](#)

[e-mail / Contact](#)

[Impressum](#)

[Allgemeine Geschäftsbedingungen](#)

Filter Types

- [Loader Filter](#)
- [STAFI](#)
- [PNEUFIX](#)
- [Containerfilter](#)
- Filter Cartridges, Inserts
- Filter Hoses
- Metal Filter Forms
- **Sack Emptying Filter With Fan**

Sack Emptying Filter with Fan

Application:

Only for **discontinuous** operation.

Specially designed for the emptying of sacks with dusty materials. For assembling directly above the material bunker.

Description:

Housing with clean air section ventilator and dusty air section filter chamber, each accessible via large service doors. The emptying compartment with removable grating is equipped with a feed opening which has to be closed during the cleaning of the envelope bag filter insert. Electromechanical dedusting via cleaning motor.

The sack emptying filter can be delivered in two different sizes.

We recommend the following:

- for short-run sack emptying size **AM 135**

- for long-term sack emptying resp. very fine particulates size **AM 235**

Type	m³/h	Pa	kW
V 31	900	1750	0,75
V 32	1500	1600	1,5
V 33	2300	1600	2,2

Type	Filter surface (m²)
135	13
225	23



[→ back to product survey](#)