

BS Vertriebsbüro GmbH

Silo-Anlagenbau - "Your specialist in silo components"

Pillauer Str. 2 · D-74336 Brackenheim
Fon ++49 (0)7135 12409 · Fax ++49 (0)7135 933599
e-mail: info@bs-vertrieb.de

[Home](#)

[e-mail / Contact](#)

[Impressum](#)

[Allgemeine Geschäftsbedingungen](#)

Silo Safety Devices / level measurement / weighing and measuring

- [Overpressure &
Vacuum Flap
Type SDAK](#)
- [Overfill Protection](#)
- [Microflex](#)
- [Microcell](#)
- **Loadstand**
- [Multistream B-80](#)
- [Multistream G](#)
- [Uniband](#)

Loadstand



Features:

- Bolt-in-place technology without rods and stay-bars
- Simple mounting and cabling work
- High output signal by semi-conductor strain gauge technology
- Safe operation with mixers and vibrators

Technical data:

Working voltage: 12 V DC
Max. overload: double nominal load
Output signal at nominal load: 400 mV
Linearity fault: W 0,2 %
Reproduction rate und hysteresis: W 0,1 %

Types and measuring ranges:

Type	Measuring range kg	Height overall mm	
S2- 025K	11.340	187	
S2- 050K	22.680	238	
S2- 100K	45.360	314	
S2- 200K	90.720	390	
S2- 300K	136.080	559	
S2- 500K	226.800	622	
S2-750K	340.200	762	
S2- 1000K	453.600	902	

Special measuring ranges and dimensions upon request.

The main feature of the **Load-Stands** is that the strain-gauge sensors can be exchanged without removing the load cells from the construction.

[→ back to product survey](#)